

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) An address resolution method for a communication system comprising a plurality of mobile packet terminals ~~(mobile stations: MS)~~, a connection oriented ~~type~~ network which accommodates the mobile packet terminals ~~(MS)~~ and supplies a connection oriented ~~type~~ communication, a connectionless ~~type~~ network having a switch node ~~(SW)~~ and an inter-working function ~~(IWF)~~ for mutually connecting the respective networks, comprising the steps of:

A' receiving data containing a ~~"Gratuitous-ARP"~~ Gratuitous-ARP packet which is ~~one type of "address resolution protocol"~~ an address resolution protocol (ARP) ~~(see IETF:Internet Engineering Task Force Document RFC826)~~, from one ~~of the mobile packet terminal (MS) terminals~~ 10 on the inter-working function ~~(IWF)~~, in ~~that a case~~ a case when ~~[[a]] the one~~ the one mobile packet terminal ~~(MS)~~ is handed over;

transmitting the packet to the connectionless ~~type~~ network on the inter-working function ~~(IWF)~~;

making the switch node ~~(SW)~~ receive ~~it~~ the packet on the inter-working 15 function ~~(IWF)~~;

~~renews~~ renewing a physical address management table provided in the switch node ~~(SW)~~ on the basis of the content of the packet on the switch node ~~(SW)~~; and

determining the inter-working function ~~(IWF)~~ at ~~the~~ a handover destination of the one mobile packet terminal ~~(MS)~~ on the switch node ~~(SW)~~. 2

2. (Currently Amended) The address resolution method as claimed in claim 1,

wherein when the handover over the inter-working function (IWF) is detected, the one mobile packet terminal (MS) creates and transmits the IP address of its own mobile packet terminal (MS) to a transmission IP (~~Internet Protocol~~) address portion of the ~~"non-group ARP"~~ a non-group ARP and a target IP address portion, and creates and transmits to a transmission physical address portion an ARP request message in which a mobile ID of its own mobile packet terminal (MS) is set.

3. (Currently Amended) The address resolution method as claimed in claim 1,

Al Cont.  
wherein when the handover over the inter-working function (IWF) is detected, the one mobile packet terminal (MS) creates and transmits the IP address of its own mobile packet terminal (MS) to a transmission IP (~~Internet Protocol~~) address portion of the ~~"non-group ARP"~~ a non-group ARP and a target IP address portion, and creates and transmits to a transmission physical address portion an ARP request message in which the telephone number of its own mobile packet terminal (MS) is set.

4. (Currently Amended) The address resolution method as claimed in claim 1,

wherein the inter-working function (IWF) uses Ethernet as the connectionless type network, and when receiving data containing the ARP request message from the one mobile packet terminal, the inter-working function (IWF) ~~converts~~ forms the data to an Ethernet frame ~~which is the optimum format to the Ethernet~~ as a physical layer of the connectionless type network and ~~transmitting~~ transmits the Ethernet frame to the connectionless type network.

5. (Currently Amended) The address resolution method as claimed in claim 1, wherein the inter-working function ~~{IWF}~~ uses as the connection oriented ~~type~~ communication system an IS-95 system which is standardized in EIA (Electronic Industries Association)/TIA (Telecommunication Industry Association), ANSI (American National Standard Institute) and CDG (CDMA Development Group) ~~serving as institutes of standards of U.S.A.~~

6. (Currently Amended) The address resolution method as claimed in claim 2,

wherein when the handover over the inter-working function ~~{IWF}~~ is detected, the one mobile packet terminal ~~{MS}~~ creates and transmits the IP address of its own mobile packet terminal ~~{MS}~~ to a transmission IP (Internet Protocol) address portion of the ~~"non-group ARP"~~ a non-group ARP and a target IP address portion, and creates and transmits to a transmission physical address portion an ARP request message in which the a telephone number of its own mobile packet terminal ~~{MS}~~ is set.

7. (Currently Amended) The address resolution method as claimed in claim 2,

wherein the inter-working function ~~{IWF}~~ uses Ethernet as the connectionless ~~type~~ network, and when receiving data containing the ARP request message from the one mobile packet terminal, the inter-working function ~~{IWF}~~ ~~converts~~ forms the data to an Ethernet frame ~~which is the optimum format to the Ethernet~~ as a physical layer of the connectionless ~~type~~ network and ~~transmitting~~ transmits the Ethernet frame to the connectionless ~~type~~ network.

8. (Currently Amended) The address resolution method as claimed in claim 2,

wherein the inter-working function ~~{IWF}~~ uses as the connection oriented ~~type~~ communication system an IS-95 system which is standardized in EIA

(Electronic Industries Association)/TIA (Telecommunication Industry Association), ANSI (American National Standard Institute) and CDG (CDMA Development Group) ~~serving as institutes of standards of U.S.A.~~

9. (Currently Amended) The address resolution method as claimed in claim 3,

wherein the inter-working function ~~{IWF}~~ uses as the connection oriented ~~type~~ communication system an IS-95 system which is standardized in EIA (Electronic Industries Association)/TIA (Telecommunication Industry Association), ANSI (American National Standard Institute) and CDG (CDMA Development Group) ~~serving as institutes of standards of U.S.A.~~

*Alt*  
10. (Currently Amended) An address resolution communication system comprising a plurality of moving mobile packet terminals ~~{MS}~~, a connection oriented ~~type~~ network which accommodates the plural mobile packet terminals ~~{MS}~~ and supplies a connection oriented ~~type~~ communication, a connectionless ~~type~~ network having a switch node ~~{SW}~~ and an inter-working function ~~{IWF}~~ for mutually connecting the respective networks to each other, the address resolution communication system comprising:

the inter-working function ~~{IWF}~~ for receiving data containing a ~~"Gratuitous-ARP"~~ Gratuitous-ARP packet which is ~~one type~~ of "address resolution ~~protocol~~" an address resolution protocol (ARP) ~~{see IETF:Internet Engineering Task Force Document RFC826}~~ from one of the mobile packet ~~terminal {MS} terminals~~ when the one mobile packet terminal ~~{MS}~~ is handed over, and transmitting the ~~"Gratuitous-ARP"~~ Gratuitous-ARP packet to the connectionless ~~type~~ network to make the switch node ~~{SW}~~ receive the ~~"Gratuitous-ARP"~~ Gratuitous-ARP packet; and

the switch node ~~{SW}~~ for renewing a physical address table provided in the switch node ~~{SW}~~ on the basis of the content of the ~~"Gratuitous-ARP"~~ Gratuitous ARP packet to specify the interworking function ~~{IWF}~~ at the a handover destination of the mobile packet terminal ~~{MS}~~.

11. (Currently Amended) The address resolution communication system as claimed in claim 10,

wherein when detecting the handover over the inter-working function (IWF), said one mobile packet terminal (MS) creates and transmits the IP address of its own mobile packet terminal (MS) to a transmission IP (~~Internet Protocol~~) address portion and a target IP address portion, and creates and transmits to a transmission physical address portion an ARP request message in which the mobile ID of its own packet terminal (MS) is set.

12. (Currently Amended) The address resolution communication system as claimed in claim 10,

*AI Cont.* wherein when the handover over the inter-working function (IWF) is detected, the one mobile packet terminal (MS) creates and transmits the IP address of its own mobile packet terminal (MS) to a transmission IP (~~Internet Protocol~~) address portion of the "~~non-group ARP~~" a non-group ARP and a target IP address portion, and creates and transmits to a transmission physical address portion an ARP request message in which a mobile ID of its own mobile packet terminal (MS) is set.

13. (Currently Amended) The address resolution communication system as claimed in claim 10,

wherein when the handover over the inter-working function (IWF) is detected, the one mobile packet terminal (MS) creates and transmits the IP address of its own mobile packet terminal (MS) to a transmission IP (~~Internet Protocol~~) address portion of the "~~non-group ARP~~" a non-group ARP and a target IP address portion, and creates and transmits to a transmission physical address portion an ARP request message in which the a telephone number of its own mobile packet terminal (MS) is set.

14. (Currently Amended) The address resolution method as claimed in claim 10,

AI Cont.  
wherein the inter-working function (IWF) uses Ethernet as the connectionless type network, and when receiving data containing the ARP request message from the one mobile packet terminal, the inter-working function (IWF) ~~converts~~ forms the data to an Ethernet frame ~~which is the optimum format to the Ethernet~~ as a physical layer of the connectionless type network and ~~transmitting~~ transmits the Ethernet frame to the connectionless type network.

15. (Currently Amended) The address resolution communication system as claimed in claim 10,

wherein the inter-working function (IWF) uses as the connection oriented type communication system an IS-95 system which is standardized in EIA (Electronic Industries Association)/TIA (Telecommunication Industry Association), ANSI (American National Standard Institute) and CDG (CDMA Development Group) ~~serving as institutes of standards of U.S.A.~~

---